

**Underlay Technical Specification**

Item Code: TANEWSUP

Issue Date: 13/08/2024

Issue No. 10

**Sponge Rubber**

**Suitable for the stretch-fit installation of carpets**

**End Use Classification (BS 5808: 1991 / BS EN 14499 : 2015): L/U, Luxury Use**

**Outline Specification\***

Nominal thickness	8.75mm (0.34")	ISO 1765
Nominal square weigh <sup>1</sup>	3424 g/m <sup>2</sup> (101 oz/yd <sup>2</sup> )	
Nominal density	391kg/m <sup>3</sup> (24.41bs/ft <sup>3</sup> )	
Nominal roll weight	37.5 kg (83 lbs)	
Nominal roll area	10.96m <sup>2</sup> (1.37m x 8.0m); 13.11 yd <sup>2</sup> (53.94" x 314.96")	

**Test Performance to BS 5808: 1991**

End Use Classification	L/U, Luxury Use	
Work of compression Minimum 50 J/m <sup>2</sup>	143 J/m <sup>2</sup>	BS 4908 & BS 4052 & ISO 2094
Retention of work of compression (min 40%)	88 %	BS 4908 & BS 4052 & ISO 2094
Loss in thickness after dynamic loading (max 15%)	3.7 %	BS 4052 & ISO 2094
Loss in thickness after static loading (max 15%)	3.3 %	ISO 3415/3416 & BS 4939
Resistance to cracking (not greater than 50mm)	Pass	EN 14499 & BS 5808

**Test Performance to US Standards**

CFD (Compression Force Deflection)	2.2 PSI @ 25% deflection. Method: 601/12151	ASTM D3676-13
CFD (Compression Force Deflection)	6.7 PSI @ 50% deflection. Method: 601/12151	ASTM D3676-13
CFD (Compression Force Deflection)	15.9 PSI @ 65% deflection. Method: 601/12151	ASTM D3676-13
Recommended Use	Moderate Traffic Class I	US Carpet Cushion Council



**Certification**



**Guarantee**

Guaranteed for the serviceable lifetime of the carpet when used in accordance with the End Use Classification.

**Notes**

\* The nominal roll dimensions have been quoted. These may vary slightly but will comply with the requirements of BS EN 14499:2015  
 † Value derived from similar product test results

**THIS PRODUCT IS PRODUCED IN A FACILITY ACCREDITED TO ISO 9001, 14001 & 45001**

**Underlay Technical Specification**

Item Code: TANEWSUP

Issue Date: 13/08/2024

Issue No. 10



**Flammability**

Hot metal nut test	Low radius of ignition	BS 4790 & BS 5287
US Methenamine Pill Test	Pass	Pill Test DOC-FF 1-70

**Other Properties and Test Performance**

Odour	No objectionable odour	
Emissions (US Carpet & Rug Institute)	Meets low VOC emission criteria Certified GLP051 Cat CC10 Rubber	US CRI Green Label Plus Programme
Antimicrobial and mildew resistant	Yes	
Colour / backing	Green / printed Textron® backing	
Packaging	Green film / gold print	
Thermal resistance (European Units)	1.00 togs	BS 4745
R value (SI Unit)	0.08	
R Value (USA Unit)	0.45	
Impact sound reduction (Delta Lw)	39dB	BS EN ISO 10140-3:2010

**GREEN CREDENTIALS**

Green Features	Description	LEED Programme
Recyclable	At the end of the underlays useful life it can be 100% recycled	MR 2.0: Points Available It can be recycled
Recycled Content	Contains not less than 3% pre-consumer recycled material	MR 4.0: Points Available Recycled Content
Indoor Air Quality	Meets or exceeds the industry standard for indoor air quality as established by the CRI Green Label Programme	IEQ 4.3: Points Available Product is Green Label Certified
Regional Materials	Production Facility Haslingden BB4 4LS, UK Where used within 500 miles of Production Facility	MR 5.0: Points Available

LEED points must be considered along with other building components and must be determined by the specifier/architect or LEED accredited professional

**Certification**



**Guarantee**

Guaranteed for the serviceable lifetime of the carpet when used in accordance with the End Use Classification.

**Notes**

- \* The nominal roll dimensions have been quoted. These may vary slightly but will comply with the requirements of BS EN 14499:2015
- ‡ Value derived from similar product test results

**THIS PRODUCT IS PRODUCED IN A FACILITY ACCREDITED TO ISO 9001, 14001 & 45001**